



## Compare NEW with OLD



- ✓ IP65 dustproof and waterproof accredited.
- ✓ Leak tight probe assembly.
- ✓ More robust carry/presentation storage case.
- ✓ Auto-break, wrist and neck safety carry, strap.
- ✓ Swivel hinges on carry/presentation case.
- ✓ Tripod mount (for fixed and gorilla tripods).
- ✓ Low battery indicator and low sensor indicator.
- ✓ Increased sensor reading range.
- ✓ Display size 24 mm high digits.
- ✓ Push button 'Auto Calibration' feature at precisely 100 ppm as well as at ambient (20.94%).
- ✓ Automatic sleep mode when not in use.
- ✓ Quick connect/disconnect leaktight fittings for gas purge tubing.
- ✓ Protective rubber housing (optional).
- ✓ PurgEye® 100 to 1000 a complete Family of Weld Purge Monitors®.

- ✗ Not IP65 dustproof nor waterproof accredited.
- ✗ Three piece probe assembly, which can leak oxygen.
- ✗ Poor quality carry case by comparison.
- ✗ No tripod mount.
- ✗ No low battery indicator.
- ✗ No low sensor indicator.
- ✗ Tiny, difficult to read display (11 mm high digits).
- ✗ No leaktight connect/disconnect fittings for gas purge tubing.
- ✗ No optional protective rubber housing.
- ✗ No automatic sleep mode when not in use.

### Competitors have Restricted Awareness of Purging.

HFT® has over 40 Years of Innovation, Design and Manufacturing Experience. Senior Metallurgical and Scientific Personnel.

Buy the right tools for the job from HFT® once only.  
We are the Weld Purging Experts. Call on us 24/7.

## Keeping your 'Eye' on the Purge!