




© HFT®

# PlugFast™

## PERIPHERAL SEALING PLUGS



HFT PIPESTOPPERS®

- Diameters from 18 to 48" Ø (457 to 1,219 mm).
- Single port series and a double port option.
- The centre stem is 2" (51 mm diameter) and is threaded to accept a 2" BSP screw cap.
- The second port is normally fitted with a 4" (100 mm) plain bore and supplied complete with a 4" (100 mm) steel drain test plug.
- This port is normally offset to the outer edge of the Peripheral Sealing Plug allowing the water to be easily drained from the pipeline after testing.



© HFT®

Both the metric and imperial sizes are with 2" BSP outlet.

Nominal pipe size		Operating range mm		Back pressure	Weight
inches	mm	min	max	PSI max	kg
18"	457	440	480	5	9.10
19"	475	465	505	5	9.74
20"	483	490	530	5	10.38
21"	533	515	555	3	11.28
22"	559	540	580	3	12.65
23"	584	565	605	3	12.87
24"	610	590	630	3	15.57
26"	660	640	680	3	17.97
27"	686	665	705	3	18.47
28"	711	690	730	3	19.90
30"	762	740	780	3	25.09
31"	787	765	805	3	27.80
32"	813	790	830	3	28.90
33"	838	815	855	3	30.12
34"	864	840	880	3	32.20
36"	914	890	930	3	35.08
38"	965	940	980	3	38.50
40"	1016	990	1030	3	42.00
42"	1067	1040	1080	3	48.00
48"	1219	1190	1230	2	88.00

PSPS Plugfast FLY ECO 30-03-2020 ME